

Mini Dome Camera

LVC-DX420HM (NTSC) LVC-DX420HP (PAL)



Feature

- Dome size : $\varnothing 80$
- 480TV Lines of Horizontal Resolution
- High Sensitivity with a Minimum Scene illumination of 0.5LUX(F1.2)
- Auto White Balance
- Excellent signal-to-noise ratio of 50dB
- Internal Synchronization
- Power supply : DC12V

Specifications

Model	LVC-DX420HM	LVC-DX420HP
Signal System	NTSC	PAL
Total Pixels No	811(H) X 508(V)	811(H) X 508(V)
Image Device	1/3" Super HAD CCD	
Lens	Fixed Lens (f=3.6 F=2.0)	
Angular Field of View	92° (f=3.7mm)	
Synchronization System	Internal	
Scanning Frequency(H)	15.734KHZ	15.625KHZ
Scanning Frequency(V)	59.94HZ	50HZ
Horizontal Resolution	480 TV Lines	
S/N Ratio	More than 50dB	
Minimum Illumination	0.5Lux (F1.2)	
Video Output Signal	1Vp-p Composite (75 Ω)	
Function	Auto Gain Control	Auto
	Electronic Shutter	Electric Shutter(1/60 ~ 1/100,000) Electric Shutter(1/50 ~ 1/100,000)
	White Balance	Auto
	Auto Exposure	Auto
Power Source	DC 12V	
Power Consumption	2.2 W	
Operation Temp. / Humidity	-10°C~50°C (Humidity :0%RH _ 80%RH)	
Storage Temp. / Humidity	-20°C~60°C (Humidity :0%RH _85%RH)	
Dimension(\varnothing x H)	$\varnothing 88$ x 67.5mm	
Weight	60g	

Rear View



Dimension (unit : mm)

